

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




FIG. 1

Test Number --- 2797D-2-001A

Specimen Number -- P23222

Charpy V-Notch Toughness Using 100% Argon Shielding

Temperature, Degrees F	0	0	0	0	0	-20	-20	-20	-20	-20
------------------------	---	---	---	---	---	-----	-----	-----	-----	-----

Foot Pounds	71	61	57	65	50	41	47	50	53	56
-------------	----	----	----	----	----	----	----	----	----	----

Oxygen In Weld Deposit = .05220

Specimen Number -- P23225

Charpy V-Notch Toughness Using 90% Argon & 10% CO2 Shielding

Temperature, Degrees F	0	0	0	0	0	-20	-20	-20	-20	-20
------------------------	---	---	---	---	---	-----	-----	-----	-----	-----

Foot Pounds	39	54	28	50	40	31	38	35	28	32
-------------	----	----	----	----	----	----	----	----	----	----

Oxygen In weld Deposit = .05920

**Fig. 2**

Untitled  
FUME CHAMBER TESTING

DATE	08/28/2003	SPEC NO	F11649	TYPE	
SIZE	.052	CLASS		CO/LOG	PROJ#
SHEET/DEV		TEST/SER	2797D-1-001		WELDED BY KEB
FM SPEC		ENGR	DLD		CURRENT DCEP
WFS	338	AMPS	300	VOLTS	25.0
				ESO	1.000
				GAS	ARGON
ELECTRODE ANGLE	90	TRAVEL (IPM)	14.0	DURATION (MIN)	0.50
AIR FLOW (CFH)	45.00			MATERIAL TYPE	W

FOLLOWING RESULTS ARE AN AVERAGE OF THREE TESTS

% FUME	0.23	FGR (GMS/MIN)	0.20	MELT RATE (LB/HR)	11.62
--------	------	---------------	------	-------------------	-------

**Fig. 3**


Untitled  
FUME CHAMBER TESTING

DATE	08/28/2003	SPEC NO	F11650	TYPE	
SIZE	.052	CLASS	CO/LOG	PROJ#	
SHEET/DEV		TEST/SER	2797D-1-001	WELDED BY	KEB
FM SPEC		ENGR	DLD	CURRENT	DCEP
WFS	338	AMPS	300	VOLTS	25.0
				ESO	1.000
				GAS	90/10
ELECTRODE ANGLE	90	TRAVEL (IPM)	14.0	DURATION (MIN)	0.50
AIR FLOW (CFH)	45.00			MATERIAL TYPE	W


FOLLOWING RESULTS ARE AN AVERAGE OF THREE TESTS

% FUME	0.64	FGR (GMS/MIN)	0.55	MELT RATE (LB/HR)	11.35
--------	------	---------------	------	-------------------	-------

**Fig. 4**



**Fig. 5**




**Fig. 6**




**Fig. 7**






**Fig. 8**



**Fig. 9**



**Fig. 10**




Fig. 11




Fig. 12